

**PRECISIONE NELL'ESECUZIONE,  
VERSATILITÀ, POTENZA  
ED ECCELLENZA DI PRODOTTO.**



## **MOD. 420**

*Made in Italy*



## Caratteristiche tecniche Technical specifications

La casa costruttrice ha il diritto di modificare qualsiasi caratteristica tecnica o costruttiva senza l'impegno di comunicazioni preventive.

### Produzione

Productions

2400 paia/8h

2400 pairs/8h

### Consumo all'aria

Air volume

22 litri per ciclo

Per cycle Lit 22

## Dimensioni

### Dimensions

We reserve the right to adopt any engineering or design alternation even without previous notice.

### Altezza

Height

219 cm

86,2204"

### Larghezza

Width

77 cm

30,3149"

### Profondità

Depth

85 cm

33,4645"

### Peso netto

Net Weight

415 Kg

914,91 lbs



Incavigliatrice pneumatica con capacità di inchiodare simultaneamente 11 chiodi.

Questa macchina con lavorazione Nord-Sud, presenta un piantone unico nel suo genere: composto da ganasce autoregolanti, apribili fino a 20mm, rende così il piantone compatibile con qualsiasi misura e tipo di scarpa, senza bisogno di cambiare attrezzatura aggiuntiva.

**Mod.420** è dotata di un doppio caricatore a 11 canali che permette di alloggiare chiodi di dimensione comprese tra gli 8 e i 25mm, a differenza della Mod.410 provvista di un caricatore o della Mod.430 fornita di 3 caricatori; il caricamento dei chiodi è automatico.

Il cilindro del bloccaggio potenziato assicura un'inchiodatura perfetta e facilita l'inserimento di qualsiasi lunghezza di gambale grazie al suo braccio snodato. La Mod.420 è adatta per la lavorazione goodyear.



Pneumatic gang nailing machine with the capacity to nail 11 nails simultaneously.

This machine with North-South machining, features a unique nailer jack-stand: composed of self-adjusting jaws that can be opened up to 20mm, making the jack-stand compatible with any size and type of shoe, without the need to change additional equipment.

**Mod.420** is equipped with a double 11-channel loaders that accommodates nails ranging in size from 8 to 25mm, instead of the Mod.410 equipped with one loader or the Mod.430 supplied with 3 loaders; nail loading is automatic.

The strengthened locking cylinder ensures perfect nailing and facilitates the insertion of any length of leg of the boot thanks to its articulated arm. Mod.420 is suitable for goodyear machining

## CONTATTI



### SABAL SPA

Via Tortona 34  
27029 – VIGEVANO (PV)



Tel. +39 0381 23613  
Fax. +39 0381 24307



### sito internet

[www.sabalgroupp.it](http://www.sabalgroupp.it)



### e-mail:

[sabal@sabalgroupp.it](mailto:sabal@sabalgroupp.it)

